

T6 葉片泵技術參數（輸出流量及輸入功率, 1000rpm 時）

轉速 1000 rpm，使用 HF-0 及 HF-2 石油基抗磨液壓油，油液粘度 24 cSt 時：

規格系列	泵芯規格	理論排量	輸出流量，l/min						輸入功率，kW					
	工業用/車用	Q _{th} ml/rev	0 bar	70 bar	140 bar	210 bar	240 bar	280 bar	7 bar	70 bar	140 bar	210 bar	240 bar	280 bar
C CM CP	003/B03	10.8	10.8	8.3	5.8/-	-	-	-	0.9	2.2	3.7/-	-	-	-
	005/B05	17.2	17.2	14.7	12.2/11.7	9.7	9.2/-	-	1.0	3.0	5.2/5.1	7.4	8.4/-	-
	006/B06	21.3	21.3	18.8	16.3/15.8	13.8	13.3/11.3	12.2	1.0	3.4	6.1/6.0	8.9	10.0/10.0	11.5
	008/B08	26.4	26.4	23.9	21.4/20.9	18.9	18.4/16.4	17.3	1.1	4.0	7.3/7.2	10.6	12.1/12.1	13.9
	010/B10	34.1	34.1	31.6	29.1/28.6	26.6	26.1/24.1	25.0	1.2	4.9	9.1/8.9	13.3	15.1/15.1	17.5
	012/B12	37.1	37.1	34.6	32.1/31.6	29.6	29.1/27.1	28.0	1.2	5.3	9.8/9.6	14.4	16.3/16.3	18.9
	014/B14	46.0	46.0	43.5	41.0/40.5	38.5	38.0/36.0	36.9	1.3	6.3	11.9/11.7	17.5	19.9/19.9	23.1
	017/B17	58.3	58.3	55.8	53.3/52.8	50.8	50.3/48.3	49.2	1.5	7.8	14.8/14.5	21.8	24.8/24.8	28.8
	020/B20	63.8	63.8	61.3	58.8/58.3	56.3	55.8/53.8	54.7	1.5	8.4	16.0/15.8	23.7	27.0/27.0	31.4
	022/B22	70.3	70.3	67.8	65.3/64.8	62.8	62.3/60.3	61.2	1.6	9.2	17.6/17.3	26.0	29.6/29.6	34.4
	025/B25	79.3	79.3	76.8	74.3/73.8	71.8	71.3/69.3	70.2	1.7	10.2	19.7/19.3	29.2	33.2/33.2	38.6
	028*/B28*	88.8	88.8	86.3	83.8/83.3	81.3	-	-	1.8	11.3	21.9/21.9	32.5	-	-
	031*/B31*	100.0	100.0	97.5	95.0/94.5	92.5	-	-	2.0	12.6	24.5/24.4	36.4	-	-
D DM DP	014/B14	47.6	47.6	43.6	38.6/38.3	34.6	32.6/32.1	-	1.6	6.8	12.5/12.5	18.3	20.7/20.7	-
	017/B17	58.2	58.2	54.2	49.2/48.9	45.2	43.2/42.7	-	1.7	8.0	15.0/14.9	22.0	25.0/24.9	-
	020/B20	66.0	66.0	62.0	57.0/56.7	53.0	51.0/50.5	-	1.8	8.9	16.8/16.8	24.7	28.1/28.0	-
	024/B24	79.5	79.5	75.5	70.5/70.2	66.5	64.5/64.0	-	1.9	10.5	20.0/19.9	29.4	33.5/33.4	-
	028/B28	89.7	89.7	85.7	80.7/80.4	76.7	74.7/74.2	-	2.0	11.7	22.3/22.3	33.0	37.5/37.5	-
	031/B31	98.3	98.3	94.3	89.3/89.0	85.3	83.3/82.8	-	2.1	12.7	24.3/24.3	36.0	41.0/40.9	-
	035/B35	111.0	111.0	107.0	102.0/101.7	98.0	96.0/95.5	-	2.3	14.2	27.3/27.3	40.5	46.1/46.0	-
	038/B38	120.3	120.3	116.3	111.3/111.0	107.3	105.3/104.8	-	2.4	15.2	29.5/29.4	43.7	49.8/49.8	-
	042/B42	136.0	136.0	132.0	127.0/126.7	123.0	121.0/120.5	-	2.6	17.1	33.1/33.1	49.2	56.1/56.0	-
	045/B45	145.7	145.7	141.7	136.7/136.4	132.7	130.7/130.2	-	2.7	18.2	35.4/35.3	52.6	59.9/59.9	-
	050*/B50*	158.0	158.0	154.0	149.0/148.7	145.0	-	-	2.8	19.6	38.3/38.2	56.9	-	-
E EM EP	042	132.3	132.3	127.3	122.3	117.3	115.3	-	3.3	17.4	33.0	48.5	55.2	-
	045	142.4	142.4	137.4	132.4	127.4	125.4	-	3.5	18.6	35.3	52.1	59.3	-
	050	158.5	158.5	153.5	148.5	143.5	141.5	-	3.6	20.4	39.1	57.7	65.7	-
	052	164.8	164.8	159.8	154.8	149.8	147.8	-	3.7	21.2	40.6	59.9	68.2	-
	057	179.8	179.8	174.8	169.8	164.8	162.8	-	3.9	22.9	44.1	65.2	74.2	-
	062	196.7	196.7	191.7	186.7	181.7	179.7	-	4.1	24.9	48.0	71.1	81.0	-
	066	213.3	213.3	208.3	203.3	198.3	196.3	-	4.3	26.8	51.9	76.9	87.6	-
	072	227.1	227.1	222.1	217.1	212.1	210.1	-	4.4	28.4	55.1	81.7	93.1	-
	085**	269.0	269.0	264.0	-	-	-	-	4.9	33.3	-	-	-	-

注：1) - 由於內洩漏超過 50%理論流量，故不可使用；

2) * 028 (B28)，031 (B31) 及 050 (B50) 規格的最高工作壓力（間斷）為 210 bar；

3) ** 085 規格的最高工作壓力（間斷）為 70 bar；

T6 葉片泵技術參數（輸出流量及輸入功率, 1200rpm 時）

轉速 1200 rpm，使用 HF-0 及 HF-2 石油基抗磨液壓油，油液粘度 24 cSt 時：

規格系列	泵芯規格	理論排量	輸出流量，l/min						輸入功率，kW					
	工業用	Q _{th} ml/rev	0 bar	70 bar	140 bar	210 bar	240 bar	280 bar	7 bar	70 bar	140 bar	210 bar	240 bar	280 bar
C CM CP	003	10.8	13.0	10.5	8.0	-	-	-	1.1	2.6	4.4	-	-	-
	005	17.2	20.6	18.1	15.6	13.1	12.6	11.5	1.1	3.5	6.2	8.8	10.0	11.5
	006	21.3	25.6	23.1	20.6	18.1	17.6	16.5	1.2	4.1	7.3	10.5	11.9	13.8
	008	26.4	31.7	29.2	26.7	24.2	23.7	22.6	1.3	4.8	8.7	12.7	14.4	16.6
	010	34.1	40.9	38.4	35.9	33.4	32.9	31.8	1.4	5.9	10.9	15.9	18.1	20.9
	012	37.1	44.5	42.0	39.5	37.0	36.5	35.4	1.4	6.3	11.7	17.2	19.5	22.6
	014	46.0	55.2	52.7	50.2	47.7	47.2	46.1	1.5	7.6	14.2	20.9	23.8	27.6
	017	58.3	70.0	67.5	65.0	62.5	62.0	60.9	1.7	9.3	17.7	26.1	29.7	34.5
	020	63.8	76.6	74.1	71.6	69.1	68.6	67.5	1.8	10.0	19.2	28.4	32.36	37.6
	022	70.3	84.4	81.9	79.4	76.9	76.4	75.3	1.9	11.0	21.0	31.1	35.5	41.2
	025	79.3	95.2	92.7	90.2	87.7	87.2	86.1	2.0	12.2	23.6	34.9	39.8	46.3
	028*	88.8	106.6	104.1	101.6	99.1			2.1	13.5	26.2	38.9		
	031*	100.0	120.0	117.5	115.0	112.5			2.3	15.1	29.4	43.6		
D DM DP	014	47.6	57.1	53.1	48.1	44.1	42.1		1.8	8.0	14.9	21.8	24.8	
	017	58.2	69.8	65.8	60.8	56.8	54.8		1.9	9.5	17.9	26.3	29.9	
	020	66.0	79.2	75.2	70.2	66.2	64.2		2.1	10.6	20.1	29.6	33.6	
	024	79.5	95.4	91.4	86.4	82.4	80.4		2.2	12.5	23.9	35.2	40.1	
	028	89.7	107.6	103.6	98.6	94.6	92.6		2.4	13.9	26.7	39.5	45.0	
	031	98.3	118.0	114.0	109.0	105.0	103.0		2.5	15.1	29.1	43.1	49.1	
	035	111.0	133.2	129.2	124.2	120.2	118.2		2.7	16.9	32.7	48.5	55.2	
	038	120.3	144.4	140.4	135.4	131.4	129.4		2.8	18.2	35.3	52.4	59.7	
	042	136.0	163.2	159.2	154.2	150.2	148.2		3.0	20.4	39.7	59.0	67.2	
	045	145.7	174.8	170.8	165.8	161.8	159.8		3.2	21.7	42.4	63.0	71.9	
	050*	158.0	189.6	185.6	180.6	176.6			3.3	23.5	45.8	68.2		
E EM EP	042	132.3	158.8	153.8	148.8	143.8	141.8		4.0	20.8	39.5	58.3	66.3	
	045	142.4	170.9	165.9	160.9	155.9	153.9		4.1	22.2	42.4	62.5	71.2	
	050	158.5	190.2	185.2	180.2	175.2	173.2		4.3	24.5	46.9	69.3	78.9	
	052	164.8	197.8	192.8	187.8	182.8	180.8		4.4	25.4	48.6	71.9	81.9	
	057	179.8	215.8	210.8	205.8	200.8	198.8		4.6	27.5	52.8	78.2	89.1	
	062	196.7	236.0	231.0	226.0	221.0	219.0		4.9	29.8	57.6	85.3	97.2	
	066	213.3	256.0	251.0	246.0	241.0	239.0		5.1	32.2	62.2	92.3	105.2	
	072	227.1	272.5	267.5	262.5	257.5	255.5		5.3	34.1	66.1	98.1	111.8	
	085**	269.0	322.8	317.8					5.9	40.0				

注：1) - 由於內洩漏超過 50%理論流量，故不可使用；

2) * 028 (B28)，031 (B31) 及 050 (B50) 規格的最高工作壓力（間斷）為 210 bar：

3) ** 085 規格的最高工作壓力（間斷）為 70 bar：

技術參數（輸出流量及輸入功率, 1500rpm 時）

轉速 1500 rpm，使用 HF-0 及 HF-2 石油基抗磨液壓油，油液粘度 24 cSt 時：

規格系列	泵芯規格	理論排量	輸出流量，l/min						輸入功率，kW					
	工業用/車用	Q _{th} ml/rev	0 bar	70 bar	140 bar	210 bar	240 bar	280 bar	7 bar	70 bar	140 bar	210 bar	240 bar	280 bar
C CM CP	003/B03	10.8	16.2	13.7	11.2/10.7	8.7	7.7/-	-	1.3	3.3	5.4/5.3	7.6	8.5/-	-
	005/B05	17.2	25.8	23.3	20.8/20.3	18.3	17.3/15.8	16.7	1.4	4.4	7.7/7.5	10.9	12.3/12.2	14.1
	006/B06	21.3	32.0	29.5	27.0/26.5	24.5	23.4/22.0	22.9	1.5	5.1	9.1/8.9	13.1	14.8/14.7	17.0
	008/B08	26.4	39.6	37.1	34.6/34.1	32.1	31.1/29.6	30.5	1.6	6.0	10.9/10.7	15.8	17.8/17.7	20.6
	010/B10	34.1	51.2	48.7	46.2/45.7	43.7	42.6/41.2	42.1	1.7	7.3	13.6/13.4	19.8	22.5/22.3	26.0
	012/B12	37.1	55.7	53.2	50.7/50.2	48.2	47.1/45.7	46.6	1.7	7.9	14.6/14.4	21.4	24.3/24.1	28.1
	014/B14	46.0	69.0	66.5	64.0/63.5	61.5	60.5/59.0	59.9	1.9	9.4	17.7/17.6	26.1	29.6/29.5	34.3
	017/B17	58.3	87.5	85.0	82.5/82.0	80.0	78.9/77.5	78.4	2.1	11.6	22.0/21.9	32.5	37.0/36.9	42.9
	020/B20	63.8	95.7	93.2	90.7/90.2	88.2	87.2/85.7	86.6	2.2	12.5	24.0/23.8	35.4	40.3/40.2	46.8
	022/B22	70.3	105.5	103.0	100.5/100.0	98.0	96.9/95.5	96.4	2.3	13.7	26.2/26.1	38.8	44.2/44.1	51.3
	025/B25	79.3	119.0	116.5	114.0/113.5	111.5	110.4/109.0	109.9	2.5	15.2	29.4/29.2	43.5	49.6/49.5	57.6
	028*/B28*	88.8	133.2	130.7	128.2/127.7	125.7	-	-	2.7	16.9	32.7/32.7	48.5	-	-
	031*/B31*	100.0	150.0	147.5	145.0/144.5	142.5	-	-	2.9	18.9	36.6/36.5	54.4	-	-
D DM DP	014/B14	47.6	71.4	67.4	62.4/62.1	58.4	56.4/55.9	-	2.3	10.0	18.5/18.5	27.1	30.7/30.6	-
	017/B17	58.2	87.3	83.3	78.3/78.0	74.3	72.3/71.8	-	2.5	11.8	22.2/22.2	32.6	37.0/37.0	-
	020/B20	66.0	99.0	95.0	90.0/89.7	86.0	84.0/83.5	-	2.7	13.2	24.9/24.9	36.7	41.7/41.7	-
	024/B24	79.5	119.3	115.3	110.3/110.0	106.3	104.3/103.8	-	2.9	15.6	29.7/29.6	43.7	49.8/49.8	-
	028/B28	89.7	134.6	130.6	125.6/125.2	121.6	119.6/119.0	-	3.1	17.4	33.2/33.2	49.1	55.9/55.9	-
	031/B31	98.3	147.5	143.5	138.5/138.1	134.5	132.5/131.9	-	3.2	18.9	36.2/36.2	53.6	61.1/61.0	-
	035/B35	111.0	166.5	162.5	157.5/157.2	153.5	151.5/151.0	-	3.4	21.1	40.7/40.7	60.3	68.7/68.7	-
	038/B38	120.3	180.5	176.5	171.5/171.1	167.5	165.5/164.9	-	3.6	22.7	43.9/43.9	65.2	74.3/74.3	-
	042/B42	136.0	204.0	200.0	195.0/194.7	191.0	189.0/188.5	-	3.9	25.5	49.4/49.4	73.4	83.7/83.7	-
	045/B45	145.7	218.6	214.6	209.6/209.2	205.6	203.6/203.0	-	4.0	27.2	52.8/52.8	78.5	89.5/89.5	-
	050*/B50*	158.0	237.0	233.0	228.0/227.7	224.0	-	-	4.3	29.3	57.1/57.0	85.0	-	-
E EM EP	042/042	132.3	198.5	193.5	188.5	183.5	181.5	-	5.2	26.2	49.4	72.7	82.7	-
	045/045	142.4	213.6	208.6	203.6	198.6	196.6	-	5.4	27.9	52.9	78.0	88.8	-
	050/050	158.5	237.8	232.8	227.8	222.8	220.8	-	5.7	30.7	58.6	86.5	98.4	-
	052/052	164.8	247.2	242.2	237.2	232.2	230.2	-	5.8	31.8	60.8	89.8	102.2	-
	057/057	179.8	269.7	264.7	259.7	254.7	252.7	-	6.0	34.5	66.0	97.6	111.2	-
	062/062	196.7	295.1	290.1	285.1	280.1	278.1	-	6.3	37.4	71.9	106.5	121.3	-
	066/066	213.3	320.0	315.0	310.0	305.0	303.0	-	6.6	40.3	77.8	115.2	131.3	-
	072/072	227.1	340.7	335.7	330.7	325.7	323.7	-	6.9	42.7	82.6	122.5	139.6	-
	085/085**	269.0	403.5	398.5	-	-	-	-	7.6	50.1	-	-	-	-

注：1) - 由於內洩漏超過 50%理論流量，故不可使用；

2) * 028 (B28)，031 (B31) 及 050 (B50) 規格的最高工作壓力（間斷）為 210 bar；

3) ** 085 規格的最高工作壓力（間斷）為 70 bar；

T6 葉片泵技術參數（輸出流量及輸入功率, 1800rpm 時）

轉速 1800 rpm，使用 HF-0 及 HF-2 石油基抗磨液壓油，油液粘度 24 cSt 時：

規格系列	泵芯規格	理論排量	輸出流量，l/min						輸入功率，kW					
	工業用	q _{th} ml/rev	0 bar	70 bar	140 bar	210 bar	240 bar	280 bar	7 bar	70 bar	140 bar	210 bar	240 bar	280 bar
C CM CP	003	10.8	19.4	16.9	14.4	11.9	11.4	10.3	1.7	4.0	6.4	8.9	10.0	11.5
	005	17.2	31.0	28.5	26.0	23.5	23.0	21.9	1.9	5.3	9.1	13.0	14.6	16.8
	006	21.3	38.3	35.8	33.3	30.8	30.3	29.2	1.9	6.2	10.8	15.6	17.6	20.3
	008	26.4	47.5	45.0	42.5	40.0	39.5	38.4	2.1	7.2	13.0	18.8	21.3	24.6
	010	34.1	61.4	58.9	56.4	53.9	53.4	52.3	2.2	8.9	16.2	23.6	26.8	31.0
	012	37.1	6.8	64.3	61.8	59.3	58.8	57.7	2.3	9.5	17.5	25.5	29.0	33.6
	014	46.0	82.8	80.3	77.8	75.3	74.8	73.7	2.5	11.4	21.2	31.1	35.4	41.0
	017	58.3	104.9	102.4	99.9	97.4	96.9	95.8	2.7	13.9	26.4	38.9	44.2	51.4
	020	63.8	114.8	112.3	109.8	107.3	106.8	105.7	2.8	15.1	28.7	42.3	48.2	56.0
	022	70.3	126.5	124.0	121.5	119.0	118.5	117.4	3.0	16.5	31.4	46.4	52.9	61.5
	025	79.3	142.7	140.2	137.7	135.2	134.7	133.6	3.2	18.4	35.2	52.1	59.3	69.0
	028*	88.8	159.8	157.3	154.8	152.3			3.4	20.3	39.2	58.1		
	031*	100.0	180.0	177.5	175.0	172.5			3.6	22.7	43.9	65.1		
D DM DP	014	47.6	85.7	81.7	76.7	72.7	70.7		2.9	12.1	22.3	32.5	36.9	
	017	58.2	104.8	100.8	95.8	91.8	89.8		3.1	14.4	26.8	39.2	44.5	
	020	66.0	118.8	114.8	109.8	105.8	103.8		3.3	16.0	30.1	44.1	50.1	
	024	79.5	143.1	139.1	134.1	130.1	128.1		3.6	18.8	35.7	52.6	59.9	
	028	89.7	161.5	157.5	152.5	148.5	146.5		3.8	21.0	40.0	59.0	67.2	
	031	98.3	176.9	172.9	167.9	163.9	161.9		4.0	22.8	43.6	64.5	73.4	
	035	111.0	199.8	195.8	190.8	186.8	184.8		4.2	25.4	49.0	72.5	82.5	
	038	120.3	216.5	212.5	207.5	203.5	201.5		4.4	27.4	52.9	78.3	89.2	
	042	136.0	244.8	240.8	235.8	231.8	229.8		4.8	30.7	59.5	88.2	100.5	
	045	145.7	262.3	258.3	253.3	249.3	247.3		5.0	32.7	63.5	94.3	107.5	
	050*	158.0	284.4	280.4	275.4	271.4			5.2	35.3	68.7	102.1		
E EM EP	042	132.3	238.1	233.1	228.1	223.1	221.1		6.4	31.5	59.4	87.3	99.4	
	045	142.4	256.3	251.3	246.3	241.3	239.3		6.6	33.6	63.7	93.7	106.6	
	050	158.5	285.3	280.3	275.3	270.3	268.3		6.9	37.0	70.4	103.9	118.2	
	052	164.8	296.6	291.6	286.6	281.6	279.6		7.1	38.3	73.1	107.8	122.8	
	057	179.8	323.6	318.6	313.6	308.6	306.6		7.4	41.5	79.4	117.3	133.6	
	062	196.7	354.1	349.1	344.1	339.1	337.1		7.7	45.0	86.5	127.9	145.7	
	066	213.3	383.9	378.9	373.9	368.9	366.9		8.1	48.5	93.4	138.4	157.7	
	072	227.1	408.8	403.8	398.8	393.8	391.8		8.4	51.4	99.2	147.1	167.8	
	085**	269.0	484.2	479.2					9.2	60.2				

注：1) - 由於內洩漏超過 50%理論流量，故不可使用；

4) * 028 (B28)，031 (B31) 及 050 (B50) 規格的最高工作壓力（間斷）為 210 bar：

5) ** 085 規格的最高工作壓力（間斷）為 70 bar：